



CF.125

FLANGE LOAD CELLS



- ✓ Compact design
- ✓ Easy installation
- ✓ High reliability
- ✓ Strain gauge technology
- ✓ Measuring range from 500N to 2500N


A reliable web tension control may reduce web tears in order to increase productivity. CF flange load cells, used in a precise tension control system, are designed to carry out these delicate tasks.

They are installed at the end of a measuring roller to precisely detect the resultant of the forces generated by pulling of the material depending on the wrapping angle.

CF load cells have been designed with a compact design, to easily fit them in narrow spaces, to be installed very easily and to reach a very high reliability.

Operating principle: CF load cells use the strain gauge operating principle to guarantee a perfect detection of the web tension. Strain gauges resistors are mounted on a inner metal foil of a load cell and connected to each other in a "wheatstone bridge" able to convert a mechanical movement into an electrical signal, that must be amplified by suitable amplifiers.

TECHNICAL DRAWING



Selection model table


Code	Load N
CF.125.50	500
CF.125.100	1000
CF.125.175	1750
CF.125.250	2500

* for other model contact our technical dpt.

CF.125.xx
└─ Load N
└─ Load cell model


CALCULATION

HORIZONTAL RESULTANT




$F = T \sin \alpha/2$

DOWNWARD RESULTANT



$F = T \sin \alpha/2 + P/2 \cos \beta$

UPWARD RESULTANT



$F = T \sin \alpha/2 - P/2 \cos \beta$

TECHNICAL DATA

Precision class	0.5	
Sensitivity	Normal Supply	from 1,5mV/V to 2,0mV/V 10V - max 15V
Total error-repeatability-hysteresis-linearity	< ± 0,05% end scale value	
Measuring principle	strain gauge full bridge	
Strain gauge bridge resistance	350Ω Ohm	
Max overload	300%	
Temperature range	0°C/+60°C	
Option	4-20 mA output	
Weight		

*Data are subject to technical change without notice



Re S.p.A.
via Firenze 3
20060 Bussero (MI) Italy

T +39 02 9524301
F +39 02 95038986
E info@re-spa.com

Assistenza tecnica
Technical support
T +39 02 952430.300
E support@re-spa.com

Assistenza commerciale
Sales support
T +39 02 952430.200
E sales@re-spa.com