



# SPLICE TABLE



- ✓ Easy material cutting and joining
- ✓ Many configurations for material clamping and cutting available
- ✓ Can be installed both on web guide systems or machines
- ✓ Pressure safety switch for open/close listel signaling
- ✓ Dimensions on customer's request

Re splicing table can be installed on a new or existing web guiding system or independently on the machine to allow the operator to cut and join precisely the material.

The cutting table, as necessary, can be selected among many configurations:

- Fixed or movable plate
- Pneumatic listels or pneumatic pistons for material clamping
- Plate with straight, oblique or both versions guide for the knife
- Tape holder on board for the joining
- Pressure safety switch for open/close listel signaling

Re splice table can be designed with different dimensions and on customer's request.

## CONFIGURATIONS

### Splice plate




Movable  
splice table




Fixed  
splice table


### Material cutting system



Straight and  
oblique cutting



Straight  
cutting



Oblique  
cutting

## KIT SPLICE TABLE



It is possible to order both the complete kit or single parts for applications on existing web guide systems or independently on machines

## TECHNICAL DATA

Max air pressure 2-3 bar

Movable table movement +/- 25 mm

\*Ci riserviamo modifiche tecniche



Re S.p.A.  
via Firenze 3  
20060 Bussero (MI) Italy

T +39 02 9524301  
F +39 02 95038986  
E [info@re-spa.com](mailto:info@re-spa.com)

Assistenza tecnica  
Technical support  
T +39 02 952430.300  
E [support@re-spa.com](mailto:support@re-spa.com)

Assistenza commerciale  
Sales support  
T +39 02 952430.200  
E [sales@re-spa.com](mailto:sales@re-spa.com)